## ATRV AUSSIE TRAVELLER PTY LTD

## Curved Roof Rafter

Made to our exclusive design curve and shape the Curved Roof Rafter (CRR) was developed to help overcome two of the problems users of roll out awnings face.

- It helps prevent wind flap in the fabric of the awning,
- It reduces water retention in rain.

The Curved Roof Rafter is particularly effective when used in conjunction with our Anti Flap Kit, with or without the addition of walls.



RAFTER RETRACTED FOR **TRAVEL** 



FIT POLE END INTO WALL BRACKET FIXED TO SIDE OF VAN



EXTEND OUT FRONT TELESCOPIC SECTION AND FIT SPIGOT INTO HOLE IN ROLLER



FITTED IN CONJUNCTION WITH




SHOWS CURVED ROOF RAFTER IN POSITION

## SUGGESTED USAGE

Awning Size	Number of Rafters
11' and under	1
12'	1 (2)
13'	2
14'	2
15'	2
16'	2
17'	2 (3)
18'	3
19'	3
20'	3
21'	3 (4)
22' and over	4

NB. Various brands of awnings use different vinyl fabrics which may be susceptible to some stretch when placed under tension from the Curved Roof Rafter. Aussie Traveller takes no responsibility for any fabric deformity caused by the use of the Curved Roof Rafter.




Drill a 3/8 hole 20mm down from under side of fabric.

**HEAD OFFICE AND FACTORY:** PO Box 126 Clontarf Beach QLD 4019

11-15 Oasis Court, Clontarf Phone: 07 3284 3284 Fax: 07 3284 5969 E-mail: enquiries@aussietraveller.com.au

Curved Roof Rafter Fitting Instructions



MELBOURNE SHOW ROOM

PO Box 563 Somerton Vic 3062 34-36 Merola Way, Campbellfield Ph: 03 9357 6565 Fx: 03 9357 6515

E-mail: info@aussietraveller.com.au

I00035C1/1

www.aussietraveller.com.au